

ConTour Series™ CT 115 Speaker

TWO WAY FULL RANGE SPEAKER SYSTEM

The CT 115 is a passive, extended-range speaker cabinet that can be switched between passive mode and bi-amp mode.



Its dual-function housing allows it to serve as a FOH speaker as well as a stage monitor.

The hallmarks of the CT 115 are its speech intelligibility, extraordinary phase linearity, and considerable dynamic range.

Its BEM-optimized HF horn offers precise directivity and optimal clustering without phase cancellations.

The CT 115 was developed principally for applications requiring excellent voice and music reinforcement and richly detailed audio resolution at high SPL for short-to-medium-throw distances.

The CT 115 is available in left and right versions (CT 115 L, CT 115 R).

For best audio results, we recommend using the HK DSM 2060 Controller, or the HK Digital Field Controller (DFC) in combination with a DFC network.

Connectors: 2x Speakon® NL 4

Enclosure: 18 mm (3/4"), 13-ply birch plywood

Angles up: 47° + 18° (monitor application)

Finish: Black acrylic lacquer

Grille: Metal grille with acoustic foam

Handles: 4x Ergonomic handle

Rigging hardware: 2x Aero quip fly tracks, 2x M10 threaded bushing

Pole mount: HK AUDIO Triple Tilt™, diameter 35 mm

Mounting angle: +5°, -3°, -10°

Weight: 33 kg / 72.6 lbs.

Dimensions (W x H x D): 45 cm x 69.6 cm x 39.6 cm